



 $E\text{-}mail: sales@seenlamp.com \ Website: www.seenlamp.com\\$

Trimless LED Downlight 6W


LED Downlight-COB

Version: V1.0

Model No.: SL-XQ206006 01

Date: June15th,2020





P Ø55-60

Features

- Downlights Trim Hide In Ceiling ,Elegant Looks For Modern Decoration Style.
- Optical Flexibility 15/24/36 Degree Beam Angle.
- Interchangeable Reflector In Various Finishing.
- Modular Design, Pre Build-In Frame,It Is Easy For Debugging And Maintenance.
- High Quality Aluminum Heat Sink With Excellent Thermal Dissipation.
- Ra90/95 High Color Rendering Is More Realistic, Restores The True Color Of The Subject.
- CCT Range 2700K/3000K/3500K/4000K/5000K/5500K.
- Constant Current Driver Output With Flicker Free, Led Driver Efficiency 85-90%.
- \bullet Supporting To Triac Dimming, 0/1-10V And Dali Dimming .
- 3 Years Warranty.

Application:

Widely Use In Commercial And Residential Lighting, Like Hotels, Villa, Culbs, Restaurants, Offices, Shops And Home, Etc

Luminaire Specification

| Height | H 75mm |
|--------------------|-----------|
| Bezel | Ø 85mm |
| Hole cut-out | Ø 60mm |
| Luminaire material | Aluminium |
| IP Rating | IP20/44 |

LED Specification

| LED | COB Luminus |
|---------------|--------------------------------|
| Power | 6W |
| CRI | Ra90 |
| CCT | 2700K, 3000K,3500K,4000K,5000K |
| Lumen | 450lm |
| Beam angle | 15°/24°/36° |
| Drive current | DC150mA,36V |
| Input voltage | AC220~240V/50-60Hz |
| Accessories | Honeycomb |

Ordering Information

| Bean | ı angle | LED driver brand | LED CCT | Driver type Power |
|------|------------|------------------|---------|-----------------------|
| 1 | Narrow 15° | 1 Lifud | 1 2700K | 1 Triac Dimming A 6W |
| 2 | Medium 24° | 2 Tridonic | 2 3000K | 2 0-10V Dimming |
| 3 | Wide 36° | 3 Euchips | 3 4000K | 3 DALI Dimming |
| | | | 4 5000K | 4 Regular Non-dimming |