# SEENlamp


# **Technical Data Sheet**

E-mail: sales@seenlamp.com Website: www.seenlamp.com

# Surface Mounted Led Pendant Light

Led Pendant Light -COB 6W Model No.: SL-DX104506





# Features

- 6063 Aluminum Housing Provides Excellent Thermal Dissipation .
- Anti Glare Design With Black Color Deep Baffled And Honeycomb.
- High Color Rendering Index Ra90, Restores The True Color Of The Subject.
- $\bullet$  Lamp Body Length Can Be Custom Make 250mm,300mm,500mm  $% 10^{-1}$  .
- Optical Flexibility 15°/24°/36°/50°Beam Angle, Optic Lens High Transmittance.
- Constant Current Driver With Flicker Free ,Achieves Stable Working Performance.
- Multiple Size Selection With Power From 6W To 25W.
- Sand White And Sand Black Surface Finish.Surface Treatment With Excellent Texture Feeling.
- Triac Dimming ,0/1-10V And Dali Dimming Led Driver To Supporting Smart Control.
- Quality 3 Years warranty

• Application: Suitable For Commercial And Residential Applications Like Shopping Mall, Villa, Hotels, Restaurants,Office ,Home etc.

## Luminaire Specification

| Height             | H 250mm         |
|--------------------|-----------------|
| Bezel              | Ø 45mm          |
| Installation       | Surface Mounted |
| Luminaire material | 6063 Aluminium  |
| IP Rating          | IP20            |

### **LED Specification**

| LED           | COB LUMINUS                    |
|---------------|--------------------------------|
| Power         | 6W                             |
| CRI           | Ra90                           |
| CCT           | 2700K, 3000K,3500K,4000K,5000K |
| Lumen         | 450lm                          |
| Beam angle    | 15°/24°/36°/50°                |
| Drive current | DC150mA,36V                    |
| PF            | ≥0.5                           |
| Input         | AC220~240V/50~60Hz             |
| Finish        | Sand White / Sand Black        |

#### **Ordering Information**

|   | Beam angle | LED driver brand | LED CCT | Driver type           | Power |
|---|------------|------------------|---------|-----------------------|-------|
| 1 | Narrow 15° | 1 Lifud          | 1 2700K | 1 Regular Non-dimming | A 6W  |
| 2 | Medium 24° | 2 Eaglerise      | 2 3000K | 2 Triac dimming       |       |
| 3 | Wide 36°   | 3 AI Dimming     | 3 4000K | 3 0-10V dimming       |       |
| 4 | Flood 50°  |                  | 4 5000K | 4 DALI dimming        |       |

(i) In case of any printing or translation error, we apologize for the inconvenience, as for the content change, we are sorry for no further notice.

Version: V1.0 Date: July 10th,2021