


Surface Mounted Led Pendant Light

Led Pendant Light -COB 20W

Model No.: SL-DX107020



Version: V1.0

Date: July 10th,2021

Ø 70

Features

- 6063 Aluminum Housing Provides Excellent Thermal Dissipation .
- Anti Glare Design With Black Color Deep Baffled And Honeycomb.
- High Color Rendering Index Ra90, Restores The True Color Of The Subject.
- \bullet Lamp Body Length Can Be Custom Make 250mm,300mm,500mm $\ .$
- • Optical Flexibility $\,15^{\circ}\!/24^{\circ}\!/36^{\circ}\!/50^{\circ} \text{Beam Angle, Optic Lens High Transmittance.}$
- Constant Current Driver With Flicker Free ,Achieves Stable Working Performance.
- Multiple Size Selection With Power From 6W To 25W.
- Sand White And Sand Black Surface Finish.Surface Treatment With Excellent Texture Feeling.
- Triac Dimming ,0/1-10V And Dali Dimming Led Driver To Supporting Smart Control.
- Quality 3 Years warranty
- Application: Suitable For Commercial And Residential Applications Like Shopping Mall, Villa, Hotels, Restaurants, Office , Home etc.

Luminaire Specification

Height	H 250mm
Bezel	Ø 70mm
Installation	Surface Mounted
Luminaire material	6063 Aluminium
IP Rating	IP20

LED Specification

LED	COB LUMINUS
Power	20W
CRI	Ra90
CCT	2700K, 3000K,3500K,4000K,5000K
Lumen	1450lm
Beam angle	15°/24°/36°/50°
Drive current	DC500mA,36V
PF	≧ 0.9
Input	AC220~240V/50~60Hz
Finish	Sand White / Sand Black

Ordering Information

	Beam angle	LED driver brand	LED CCT	Driver type Power
1	Narrow 15°	1 Lifud	1 2700K	1 Regular Non-dimming A 20W
2	Medium 24°	2 Eaglerise	2 3000K	2 Triac dimming
3	Wide 36°	3 AI Dimming	3 4000K	3 0-10V dimming
4	Flood 50°		4 5000K	4 DALI dimming

⁽i) In case of any printing or translation error, we apologize for the inconvenience, as for the content change, we are sorry for no further notice.